



PARKSIDE
TIMBER





Parkside Timber has been producing products by Australians for Australians for over 75 years.

Parkside Timber has a proud history of producing some of the finest quality hardwood timber products for generations and our involvement in architectural and designer based projects has been the cornerstone of our business.

Parkside Timber offers a wide variety of species and products to help the greatest of imaginations, and professionals, complete their projects.

Manufacturing a diverse range of timber products from large, heavy structural sections, floor joists and roofing timbers to value added kiln dried and dressed products such as floorboards, decking, cladding and some of the most beautiful furniture timbers you will ever find, we believe that we have the right timber for your needs, whatever they may be.

Strong, hard-wearing and incredibly beautiful.

The natural durability of the species produced plus the high manufacturing standards held by the Aussies producing Parkside Timber products makes our products some of the highest quality in the marketplace.



We are not the only ones who appreciate our timber. Parkside Timber distributes timber throughout Australia and to many countries all over the world.

New Zealand, China, Hong Kong, South Africa, Korea, Canada and the United States - all of these countries enjoy the beauty and quality of our timber.



An environmentally friendly product.

Parkside Timber is proud to manufacture products from sustainably grown plantations. Along with Parkside having CoC for their resource, timber is a naturally carbon positive product due to its ability to store carbon both during its growth phase, and even when it is processed into a building product.



Chain of Custody.

Parkside is a company who is proud to be known as a sustainably managed organisation. The hardwood timber resource used by Parkside to create such beautiful products is primarily sourced from sustainably managed Government forests, while a small percentage of resource is received from private log sellers who ensure the resource is legally managed.

At Parkside we also pride ourselves on ensuring our resource has a third party accreditation for chain of custody of resource. This Chain of Custody Certification (CoC) means the resource we use is only sourced from legal means, and ensures Parkside have a commitment to:

- Planning and monitoring of sustainability of log resource.
- Adherence to all laws associated with the land of the resource.
- Considerations of the indigenous, community and the workers rights, beliefs and values.
- Ensuring protection of environmental and ecological values.
- Assurance of ongoing forest yields and sustainability.



DECKING

QLD Species

Parkside Timber decking is perfect in any decking applications. It adds beauty, richness and depth to any commercial or residential application.



GRADES

Select | Standard | Feature



SIZES AND LENGTHS

65 | 86 | 135 x 19mm

135 x 32mm

140 x 25mm

Random packs 1.5m to 5.7m



DURABILITY

Class 1 Above Ground

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959 and BAL 19 as a minimum

Spotted Gum and Ironbark Red are fire rated to BAL 29


Chain of Custody as per AS 4707



SPECIES




QLD Spotted Gum
Hardness 11



Grey & Red Ironbark
Hardness 14



QLD Reds
Hardness 12



Mixed Blends
Hardness 10.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



DECKING

VIC & WA Species

A Parkside Timber deck provides the ideal look for both modern and classic homes, and is the perfect choice for large commercial projects. It offers a very attractive appearance to compliment any architectural style and decor.



GRADES

Select | Standard | Feature



SIZES AND LENGTHS

65 | 86 | 135 x 19mm

135 x 32mm (Silvertop Ash)

Random packs 1.5m to 5.7m



DURABILITY

Class 2 Above Ground



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959


Silvertop Ash is rated to BAL 29.

Karri and Jarrah can achieve BAL 29 when used in conjunction with non-combustible wall cladding and enclosed subfloor


Chain of Custody as per AS 4707



SPECIES



Silvertop (VIC)
Hardness 9.5



Karri (WA)
Hardness 9.0



Jarrah (WA)
Hardness 8.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



PRE-OILED FINGER JOINTED DECKING

QLD & WA Species

Parkside Timber decking is now available finger jointed for straightness and pre-oiled for dimensional stability.



GRADES

Standard & Better



SIZES AND LENGTHS

86 | 135 x 19mm

Set length 5.7m



DURABILITY

Spotted Gum

Class 1 Above Ground


ACQ H3 Treatment

Karri • Jarrah


Class 2 Above Ground



SPECIES



QLD Spotted Gum
Hardness 11



Karri (WA)
Hardness 9.0



Jarrah (WA)
Hardness 8.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959
Spotted Gum is fire rated to BAL 29
Karri and Jarrah can achieve BAL 29
when used in conjunction with non-combustible wall cladding and enclosed subfloor

Chain of Custody as per AS 4707



FLOORING & OVERLAY

QLD Species

Parkside Timber flooring includes a stunning range of tongue and groove solid timber flooring and can be matched to renovated floors or prepared for new floor construction.



GRADES

Select | Standard | Feature



SIZES AND LENGTHS

80 | 130 x 19mm

75 | 125 x 14mm

Solid flooring lengths 0.9m to 5.9m

Overlay flooring lengths 0.6m to 2.1m



DURABILITY

Class 1 Above Ground



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959 and BAL 19 as a minimum

Spotted Gum and Ironbark Red are fire rated to BAL 29

Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum
Hardness 11



Grey & Red Ironbark
Hardness 14



QLD Reds
Hardness 12



Mixed Blends
Hardness 10.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



FLOORING & OVERLAY

VIC Species

Parkside Timber flooring is hard enough to outlast your great grandchildren and is fast becoming the most beautiful and durable flooring product in Australia.



GRADES

Select | Standard | Wormy



SIZES AND LENGTHS

85 | 130 x 19mm (End Matched)

85 | 130 x 14mm (Overlay Plain End)

180 x 19mm (Plain End)

Solid flooring lengths 0.9m to 5.9m

Overlay flooring lengths 0.4m to 3.0m



DURABILITY

Australian Chestnut - Wormy Chestnut - Southern Ash

Class 3 Above Ground



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959

Chain of Custody as per AS 4707



SPECIES



Southern Ash
Hardness 5.8



Australian Chestnut
Hardness 8.1



Wormy Chestnut®
Hardness 8.1

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



FLOORING & OVERLAY

WA Species

Parkside Timber flooring is hard wearing and is sure to remain a centrepiece in your home for generations.



GRADES

Standard & Better | Feature



SIZES AND LENGTHS

80 | 130 x 19mm (End Matched)

85 | 130 x 13mm (Overlay Plain End)

Solid flooring lengths 0.9m to 5.9m

Overlay flooring lengths 0.6m to 3.0m



DURABILITY

Class 2 Above Ground



CERTIFICATION

Manufactured to comply with AS 2796


Fire rated in accordance with AS 3959

Karri and Jarrah can achieve BAL 29 when used in conjunction with non-combustible wall cladding and enclosed subfloor

Chain of Custody as per AS 4707



SPECIES



Karri
Hardness 9.0



Jarrah
Hardness 8.5

Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



CLADDING

QLD SPECIES

Parkside cladding provides an attractive and economical way to finish the exterior and interior of both new and old buildings.



GRADES

Select I Standard



SIZES AND LENGTHS

Shiplap 125 x 19mm (End Matched)



DURABILITY

Class 1 Above Ground

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959 and BAL 19


Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum



Mixed Ironbark



GL18 POSTS QLD SPECIES

Parkside GL18 posts are a beautiful feature for any home, backyard deck or gazebo. Produced from QLD Spotted Gum, they are an attractive feature for any home.



GRADES

Select



SIZES AND LENGTHS

90 x 90mm

100 x 100mm

115 x 115mm

135 x 135mm

Lengths 2.4m, 2.7m, 3.0m, 3.6m, 4.2m, 4.8m & 5.4m



DURABILITY

Class 1 Above Ground

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 1328.1:1988

GLTAA certified posts

Fire rated in accordance with AS 1720.4 and BAL 29

Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum

APPLICATIONS

- Verandah posts
- Patio posts

GLTAA CERTIFICATION

Parkside have invested in third party accreditation for our GL18 Spotted Gum laminated posts through internationally recognised organisation, the Glue Laminated Timber Association of Australia (GLTAA).

This certification confirms Parkside GL18 posts adhere to and perform at a minimum to the Australian standards in AS 1328, giving customers peace of mind that Parkside GL18 posts will perform in their specified applications.



GL20 BEAMS QLD SPECIES

Parkside GL20 beams are not only strong, but will provide your home with a stylish impact statement.



GRADES

Select



SIZES AND LENGTHS

140 | 190 | 240 | 290 x 65mm

Lengths 3.6m, 4.8m, 5.4m & 6.0m



DURABILITY

Class 1 Above Ground

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 1328.1:1988

GLTAA certified beams

Fire rated in accordance with AS 1720.4 and BAL 29

Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum

APPLICATIONS

- Lintels
- Bearers
- Beams
- Rafters
- Columns

GLTAA CERTIFICATION

Parkside have invested in third party accreditation for our GL20 Spotted Gum laminated beams through internationally recognised organisation, the Glue Laminated Timber Association of Australia (GLTAA).

This certification confirms Parkside GL20 beams adhere to and perform at a minimum to the Australian standards in AS 1328, giving customers peace of mind that Parkside GL20 beams will perform in their specified applications.



F27 HARDWOOD QLD SPECIES

Parkside F27 seasoned structural hardwood is extremely strong and durable. It offers excellent structural integrity as well as a decorative and functional finish.



SIZES AND LENGTHS

70 | 90 | 140 | 190 x 35mm

70 | 90 | 140 | 190 | 240 x 45mm

Lengths 0.9m to 6.0m



DURABILITY

Class 1 Above Ground

ACQ H3 Treatment



CERTIFICATION

Manufactured to comply with AS 2082

Spotted Gum is fire rated to BAL 29

Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum



Grey & Red Ironbark
(Limited)

APPLICATIONS

- External deck joists
- Exposed beams
- Large lintels
- Appearance beams internally and externally
- Handrails
- Outdoor furniture



STRUCTURAL WA SPECIES

Parkside structural is a proven performer when used in structural applications, it's capable of spanning long distances with a minimal amount of support.



GRADES

Structural 3 and better



SIZES AND LENGTHS

Please contact your local Parkside

Timber representative for size availability.



DURABILITY

Class 2 Above Ground



CERTIFICATION

Chain of Custody as per AS 4707

Graded in accordance with Australian Standard 2082



SPECIES



Green Structural Karri



Jarrah Structural

APPLICATIONS

- Bridges
- Wharf timbers
- Railway crossings
- Sleepers
- Roofing timbers
- Pergolas



STRUCTURAL GOS F14

QLD SPECIES

Parkside GOS F14 graded timbers are strong, stable and durable for high strength applications.



SIZES AND LENGTHS

Available in a wide range of small to large end section sizes.

Available in job lots and pack lots.



DURABILITY

Class 1 Above Ground



CERTIFICATION

Manufactured to comply with AS 2082

Fire rated in accordance with AS 1720.4 and can be up to BAL 29 upon request


Chain of Custody as per AS 4707



SPECIES



QLD Spotted Gum



Grey & Red Ironbark



Forest Red Gum

APPLICATIONS

- Decking joists
- Bearers
- Structural members
- Commercial decking



SCREENING QLD & WA SPECIES

Parkside screening provides finishing touches to any aspect of architectural or landscape design.



SIZES AND LENGTHS

Karri · Jarrah

65 | 86 | 135 x 19mm

Spotted Gum

65 | 86 x 19mm

Pencil round 4 edges



DURABILITY

Karri · Jarrah

Class 2 Above Ground

Spotted Gum

Class 1 Above Ground




CERTIFICATION


Chain of Custody as per AS 4707



SPECIES



Karri



Jarrah



Spotted Gum

APPLICATIONS

- Screens
- Fencing
- Wall panels and features



JOINERY WA & VIC SPECIES

Parkside joinery timber is extremely durable hardwood, renowned for its strength and beauty.




GRADES

Karri · Jarrah Standard & Better | Feature


Wormy Chestnut Wormy



SPECIES



Karri



Jarrah



Wormy Chestnut



SIZES AND LENGTHS

100 | 150 | 200 x 25mm

100 | 150 | 200 x 38mm

100 | 150 | 200 x 50mm



DURABILITY

Karri · Jarrah

Class 2 Above Ground

Wormy Chestnut

Class 3 Above Ground

*Jarrah is a highly durable hardwood with natural flame resistant properties. When used in exterior applications it exhibits excellent termite and rot resistance.

APPLICATIONS

- Stair treads
- Door and window frames
- Furniture
- Internal joinery



CERTIFICATION

Chain of Custody as per AS 4707



PARKSIDE TIMBER